


FIND YOUR BB STANDARD

		Press Fit Model			Threaded		
A	Intern Diameter (B) Shell width (A)	41	42	46	34.8	36	47
		68 / 73		BB30	PF30	BSA	
	70					ITA	
	76.75						T47 77 A
	85.5/86.5/91.5						T47 85.5
	86.5	BB86		BB386			
	89.5/92	PF MTB		BB386			



A - Shell width (mm)

B - Internal shell diameter (mm).
With or without thread.

*Bottom brackets not highlighted in gray will be available in 2023.

FIND YOUR CRANKSET STANDARD

C	Crankset Diameter	Crankset Brand	Crankset Models
		24 mm	Shimano
	29 mm	Sram DUB	AXS Red, Force, Rival
	30 mm	Praxis, FSA, Rotor, Cane Creek	Cane creek eeWings, Rotor 3DF ROAD CRANKSET, Rotor cranks with Road axle standard, FSA K-Force, FSA Energy, FSA Gossamer, FSA SL-K



To make it easier for you to find your compatible Nova Ride bottom bracket, the best solution is to refer to your bike manufacturer's technical data sheet and identify the bottom bracket reference. If you have any doubts about the compatibility of your crankset or your bottom brackets reference, do not hesitate to email us at info@novatoride.com for more infos.

FIND YOUR BB FRAME REFERENCE

REFERENCE NAME	OTHER NAMES	MOSTLY USED BY**
BB30		Cannondale
BSA	BSC, BC 1.37" X 24 TPI, English Threaded, Threaded BB	Specialized
BB86	PF86, PF41, PF24	Canyon, Giant, Scott, BMC
T47 68/73	T47 External Road (T47 E.R), T47 External Bearing (T47 E.B), M47 X 1	Argonaut Cycles
T47 85.5	T47 Internal Road (T47 I.R), T47 Internal Bearing (T47 I.B)	Trek
T47 77 A	T47 Asymmetric	Factor
ITA	Italian Threaded, 1.375" X 24 TPI	Pinarello
PF30	PressFit30	Cannondale
BB386	BB386 EVO	Open, 3T, Orbea, Ceepo
PF MTB	PF92, BB92	Canyon, Giant, Scott, BMC, Trek

*Bottom brackets not highlighted in gray will be available in 2023.

**Mostly used but not mandatory, please double check the product sheet before buying.